

Traversprofil nr:	1	2	3	4	5	6	9	7	8
Høyde:	107mm	120mm	160mm	180mm	210mm	230mm	260mm	230mm	160mm
Bredde:	57,5mm	80mm	107mm	65mm	65mm	83mm	95mm	160mm	160mm
Vekt pr. mtr.:	3,857 kg/m	6,707kg/m	11,17 kg/m	6,438kg/m	8,653 kg/m	10,52 kg/m	15,455 kg/m	22,255 kg/m	16,982 kg/m
Tegning:	12-A410	12-A417	12-A572	12-A869	12-A868	12-A946	12-A1358	12-A947	12-A1219
Motst.mom.	Wx: 37 610 mm ³ Wy: 21 156 mm ³	Wx: 77 745 mm ³ Wy: 46 050 mm ³	Wx: 174 984 mm ³ Wy: 114 659 mm ³	Wx: 120 959 mm ³ Wy: 42 787 mm ³	Wx: 180 548 mm ³ Wy: 55 966 mm ³	Wx: 255 463 mm ³ Wy: 87 559 mm ³	Wx: 373 823 mm ³ Wy: 154 802 mm ³	Wx: 609 884 mm ³ Wy: 345 746 mm ³	Wx: 276 271 mm ³ Wy: 269 224 mm ³
Tregm.mom	Ix: 2 049 762 mm ⁴ Iy: 645 887 mm ⁴	Ix: 4 742 488 mm ⁴ Iy: 2 038 192 mm ⁴	Ix: 14 173 740 mm ⁴ Iy: 6 558 528 mm ⁴	Ix: 10 210 211 mm ⁴ Iy: 1 497 579 mm ⁴	Ix: 18 961 229 mm ⁴ Iy: 1 958 820 mm ⁴	Ix: 28 330 873 mm ⁴ Iy: 3 852 584 mm ⁴	Ix: 49 796 982 mm ⁴ Iy: 7 738 580 mm ⁴	Ix: 67 111 720 mm ⁴ Iy: 28 524 112 mm ⁴	Ix: 22 101 736 mm ⁴ Iy: 21 543 364 mm ⁴
Senteravst. for I_x:	C _x : 54,5mm	C _x : 61mm	C _x : 81 mm	C _x : 84,41 mm	C _x : 105,02 mm	C _x : 110,9 mm	C _x : 133,21 mm	C _x : 110,04 mm	C _x : 79,98 mm
Senteravst. for I_y:	Cy : 30,53mm	Cy : 44,26mm	Cy :57,2 mm	Cy :35 mm	Cy :35 mm	Cy :44 mm	Cy :50 mm	Cy :82,5 mm	Cy :80 mm
Areal:	1428 mm ²	2484 mm ²	4137 mm ²	2384,87 mm ²	3205 mm ²	3896,5 mm ²	79204 mm ²	8242,7 mm ²	6289,9 mm ²
Legering: EN-AW	AlMgSi 6005A-T6	AlMgSi 6082-T6	AlMgSi 6082-T6	AlMgSi 6005A-T6	AlMgSi 6082-T6	AlMgSi 6082-T6	AlMgSi 6082-T6	AlMgSi 6082-T5	AlMgSi 6082-T6
Min. flytegr.0,2:	225 N/mm ²	255 N/mm ²	255 N/mm ²	225 N/mm ²	255 N/mm ²	255 N/mm ²	255 N/mm ²	255 N/mm ²	255 N/mm ²
Min. bruddgrense:	270 N/mm ²	295 N/mm ²	295 N/mm ²	270 N/mm ²	295 N/mm ²	295 N/mm ²	295 N/mm ²	295 N/mm ²	295 N/mm ²