

Traversprofil nr:	1	2	3	4	5	6	9	7	8
Høyde:	107mm	120mm	160mm	180mm	210mm	230mm	260mm	230mm	160mm
Bredde:	57,5mm	80mm	107mm	65mm	65mm	83mm	95mm	160mm	160mm
Vekt pr. mtr.:	3,857 kg/m	6,707kg/m	11,238 kg/m	6,438kg/m	8,653 kg/m	10,520 kg/m	15,455 kg/m	22,255 kg/m	16,982 kg/m
Tegning:	12-A410	12-A417	12-A572	12-A869	12-A868	12-A946	12-A1385	12-A947	12-A1219
Motst.mom.	Wx: 37 610 mm ³ Wy: 21 156 mm ³	Wx: 77 745 mm ³ Wy: 46 050 mm ³	Wx: 176 425 mm ³ Wy: 114 777 mm ³	Wx: 120 959 mm ³ Wy: 42 787 mm ³	Wx: 180 548 mm ³ Wy: 55 966 mm ³	Wx: 255 463 mm ³ Wy: 87 559 mm ³	Wx: 373 823 mm ³ Wy: 154 802 mm ³	Wx: 609 884 mm ³ Wy: 345 746 mm ³	Wx: 276 271 mm ³ Wy: 269 224 mm ³
Tregm.mom	Ix: 2 049 762 mm ⁴ Iy: 645 887 mm ⁴	Ix: 4 742 488 mm ⁴ Iy: 2 038 192 mm ⁴	Ix: 14 286 920 mm ⁴ Iy: 6 593 950 mm ⁴	Ix: 10 210 211 mm ⁴ Iy: 1 497 579 mm ⁴	Ix: 18 961 229 mm ⁴ Iy: 1 958 820 mm ⁴	Ix: 28 330 873 mm ⁴ Iy: 3 852 584 mm ⁴	Ix: 49 796 982 mm ⁴ Iy: 7 738 580 mm ⁴	Ix: 67 111 720 mm ⁴ Iy: 28 524 112 mm ⁴	Ix: 22 101 736 mm ⁴ Iy: 21 543 364 mm ⁴
Senteravst. for I_x:	C _x : 54,50mm	C _x : 61,00mm	C _x : 80,98mm	C _x : 84,41mm	C _x : 105,02mm	C _x : 110,90mm	C _x : 133,21mm	C _x : 110,04mm	C _x : 80,00mm
Senteravst. for I_y:	C _y : 30,53mm	C _y : 44,26mm	C _y : 57,45mm	C _y : 35,00mm	C _y : 35,00mm	C _y : 44,00mm	C _y : 49,99mm	C _y : 82,50mm	C _y : 80,02mm
Areal:	1428,0 mm ²	2484,0 mm ²	4162,0 mm ²	2384,8 mm ²	3205,0 mm ²	3896,5 mm ²	5724,2 mm ²	8242,7 mm ²	6289,9 mm ²
Legering: EN-AW	AlMgSi 6005A-T6	AlMgSi 6082-T6	AlMgSi 6082-T6	AlMgSi 6005A-T6	AlMgSi 6082-T6	AlMgSi 6082-T6	AlMgSi 6082-T6	AlMgSi 6082-T6	AlMgSi 6082-T6
Min. flytegr.0,2:	215 N/mm ²	250 N/mm ²	250 N/mm ²	215 N/mm ²	250 N/mm ²	250 N/mm ²	250 N/mm ²	250 N/mm ²	250 N/mm ²
Min. bruddgrense:	255 N/mm ²	290 N/mm ²	290 N/mm ²	255 N/mm ²	290 N/mm ²	290 N/mm ²	290 N/mm ²	290 N/mm ²	290 N/mm ²

Alle profiler er eloksert i Brun farge: EC517 eller Hx-40
Tykkelse eloksering: 15 µm