

## 2836899 - Bæretravers TE5TS

|                  |                        |
|------------------|------------------------|
| Mastetype        | E-mast                 |
| Masteavstand     |                        |
| Faseavstand      | 0,5m                   |
| Stolpeinnfesting | 280mm-enkel masteklave |

## Traversprofil P1 (stående)

|                                               |                                                        |
|-----------------------------------------------|--------------------------------------------------------|
| Vekt: (kg/m)                                  | 3.857                                                  |
| Areal: (mm <sup>2</sup> )                     | 1428                                                   |
| Materiale:                                    | Aluminiumsprofil, bruneloksert                         |
| Legering:                                     | AlMgSi 6005A-T6                                        |
| Motstandsmoment: (mm <sup>3</sup> )           | W <sub>x</sub> = 37 608<br>W <sub>y</sub> = 21 153     |
| Annet arealmoment: (mm <sup>4</sup> )         | I <sub>x</sub> = 2 049 632<br>I <sub>y</sub> = 645 852 |
| Senteravstand for I <sub>x</sub> : (mm)       | C <sub>x</sub> = 54,50                                 |
| Senteravstand for I <sub>y</sub> : (mm)       | C <sub>y</sub> = 30,53                                 |
| Minimum flytegrense 0,2: (N/mm <sup>2</sup> ) | 215                                                    |
| Minimum bruddgrense: (N/mm <sup>2</sup> )     | 255                                                    |





