

## 2837445 - Anch. crossbar T3A-3030BH-3S

|                |                       |
|----------------|-----------------------|
| Cross arm type | Triple pole           |
| Pole distance  | 3m                    |
| Phase distance | 3m                    |
| Pole fastening | Bolt with bolt sleeve |

### Crossbar profile P3 (standing)

|  |   |
|--|---|
| Weight: (kg/m)                                   | 11.238  |
| Cross section: (mm <sup>2</sup> )                | 4162  |
| Material:  | Extruded aluminum, brown anodized                         |
| Alloy:   | AlMgSi 6082-T6  |
| Moment of resistance: (mm <sup>3</sup> )         | W <sub>x</sub> = 176 412<br>W <sub>y</sub> = 114 771      |
| Area moment of inertia: (mm <sup>4</sup> )       | I <sub>x</sub> = 14 286 921<br>I <sub>y</sub> = 6 593 950 |
| Center distance for I <sub>x</sub> : (mm)        | C <sub>x</sub> = 80,99                                    |
| Center distance for I <sub>y</sub> : (mm)        | C <sub>y</sub> = 57,45                                    |
| Minimum yield strength 0,2: (N/mm <sup>2</sup> ) | 250   |
| Minimum breaking load: (N/mm <sup>2</sup> )      | 290   |



